



Radiator Flush



Art. no	Volume	Items per unit	Items per pallet
AD25250	250 ml		
AD25999	1000 L		

Description

MPM radiator flush is used to completely clean and remove any contamination within the entire cooling system.

Main Benefits

- Superior cleaning agents clean and flush the entire cooling system.
- Removes sludge, rust and other deposits.
- Prevents build-up of acid contamination.
- Does not harm rubber hoses, metal parts and gaskets.
- Is not poisonous and does not contain acids.

Application

Suitable for all petrol, diesel and LPG engines cooling systems with radiators made of aluminum, plastic or steel.

Mixable with water, cooling fluids and conventional anti-freeze.

Instruction

- ❖ Shake well before use.
- ❖ Add contents of one 250ml bottle to the cooling system then drive for approximately 30 minutes and finally drain the cooling system.
- ❖ Flush with water and refill the cooling system with the OEM recommended fluid specification as per manufacturer's requirements.
- ❖ The contents of one 250ml bottle is suitable to treat cooling systems up to 12 litres.

Attention:

Be careful whilst opening or draining the radiator / cooling system as hot coolant or steam may escape / vent from the system.

Typical Characteristics

Density	1,0	Kg/l
PH-value	9,5 – 10,5	
Colour	Neutral /colorless to yellowish	
Odour	Neutral	